



Universal Lifting Solution

Designed to work with any GET under 750kg,
making the maintenance process faster and safer.



The Universal Lifting Solution with its simple, and easy to use design provides a safe and consistent lifting solution that works without improvisation or additional tooling.

- Eliminates unreliable slings and other improvised lifting devices
- Works with all GET regardless of size, condition, or manufacturer
- Rated load limit of 750kg (1,653lbs)
- Compact and easy to use – no additional tooling required

The Proven Solution

⊕ Key Features

Ground Engaging Tools can be heavy and awkward to handle, especially when worn. Studies have shown up to 32% of injuries in surface mining are caused by strenuous movements. By eliminating unreliable slings and other improvised lifting devices, the universal lifting solution prevents flings and drops, reducing safety hazards and keeping our customers safe.

UP TO
32% of injuries in surface mining occur
due to strenuous movements.



*750kg capacity of large hook.
Small hook capacity of 530kg.

Thoroughly Universal

Our universal lifting tool can lift any GET, from teeth to shrouds and everything in between. Regardless of size, manufacturer, or condition, it's ready for the task at hand.



A Safety Solution For All

We know that not every mine site has access to additional safety equipment. The universal lifting solution is a compact safety device that works with any D-shackle configuration with no tooling required.



Strong and Powerful

The universal lifting hook makes moving heavy GET a breeze. Multiple hook sizes can handle any application, and with a load limit of 750kg (1,653lbs) no component is out of reach.



United in performance. Inspired by innovation.

Performance unites us, innovation inspires us, and commitment drives us to keep moving forward. Count on Epiroc to deliver the solutions you need to succeed today and the technology to lead tomorrow.



(+61) 1800 987 525



(+1) 866 276 4637



globalsales@crmining.com



epiroc.com